



TYPICAL PROPERTY DATA SHEET
Buckeye Polymers Impact PP Grades

Product Information:	Black Polypropylene Copolymer good for general purpose programs requiring moderate impact resistance	Appearance:	Black
Product Features:	<ul style="list-style-type: none"> * Improved Impact Resistance * UV resistance * Chemical Resistance * High Melt Flow ranges for improved processability 	Forms:	Pellets-strand or gala cut
		Processing Method:	Injection Molding
		Processing Guide available upon request.	

Material	MFI	Ash Content	Specific Gravity	Flex Modulus	Tensile Strength	Notched Izod
Nominal values	g/10 min	%	g/cc	PSI	PSI	ft-lbs/in
BP PPC 0210 R BLK	12	5	0.94	68,150	1,740	3
BP PPC 0120 R GREY	18	14	0.98	130,000	2,000	1.0
BP PPC 0220 BLK	20	4	0.96	150,000	1,800	1.6
BP PPC 0225 BLK	25	2	0.96	130,000	1,825	2
BP RPPC 0235 CR BLK	30	6	0.97	162,000	2,200	2.0
BP RPP 0233 R BLK	35	3	0.95	125,000	1,775	3

Typical values should not be construed as a guarantee analysis of any specific lot or as specification items. The properties of any single lot or shipment of product may vary from the above typical analysis. All information contained herein is accurate and to the best of our knowledge. However, Buckeye Polymers, Inc. assumes no liability, nor makes any guarantee to the accuracy or completeness of the information contained herein. Final determination as to the suitability of any information, or use of material, is solely the responsibility of the user.

Buckeye Polymers can custom compound a material to meet your specifications.

**Buckeye
Polymers, Inc.**

104 Lee Street
 Lodi, Ohio 44254
 Phone (330)948-3007
 Fax (330)948-2037
www.buckeyepolymers.com